AlsaPlayer

0.99.80

Generated by Doxygen 1.5.5

Sat Jun 7 18:40:39 2008

Contents

1 Data Structure Index **1**

1.1 Data Structures 1

2 File Index **3**

2.1 File List 3

3 Data Structure Documentation **5**

3.1 _input_object Struct Reference 5

3.2 _input_plugin Struct Reference 7

3.3 _interface_plugin Struct Reference 9

3.4 _output_plugin Struct Reference 10

3.5 _scope_plugin Struct Reference 13

4 File Documentation **15**

4.1 input_plugin.h File Reference 15

4.2 interface_plugin.h File Reference 21

4.3 output_plugin.h File Reference 23

4.4 scope_plugin.h File Reference 25

Chapter 1

Data Structure Index

1.1 Data Structures

Here are the data structures with brief descriptions:

_input_object 5
_input_plugin 7
_interface_plugin 9
_output_plugin 10
_scope_plugin 13

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

input_plugin.h 15
interface_plugin.h 21
output_plugin.h 23
scope_plugin.h 25

Chapter 3

Data Structure Documentation

3.1 _input_object Struct Reference

`#include <input_plugin.h>`

Data Fields

- int ready
- int flags
- int nr_frames
- int nr_tracks
- int nr_channels
- int frame_size
- void * local_data
- char * path
- pthread_mutex_t object_mutex

3.1.1 Detailed Description

This is a structure that keeps frequently used parameters of an input instance. It also contains a pointer to any local_data that might be allocated by the plugin itself.

3.1.2 Field Documentation

3.1.2.1 int _input_object::ready

Flag that should be set to 1 if your plugin is ready to accept play_frame() callback

3.1.2.2 int _input_object::flags

Stream specific flags that should be set in the open() call. Read the description of the P_* definitions for details.

3.1.2.3 int _input_object::nr_frames

The total number of frames in the stream. Should be set in the open() call.

3.1.2.4 int _input_object::nr_tracks

The number of tracks, if any, in the stream. Should be set in the open() call.

3.1.2.5 int _input_object::nr_channels

The number of PCM channels in the stream. Should always be 2 at this time.

3.1.2.6 int _input_object::frame_size

The frame size in bytes. play_frame() will be called with this value.

3.1.2.7 void* _input_object::local_data

If your plugin needs extra space for its own variables assign the allocated data structure to this pointer

3.1.2.8 char* _input_object::path

Path of the currently played file

3.1.2.9 pthread_mutex_t _input_object::object_mutex

The object mutex. Used to lock and unlock the data structures. Initialized and called from the HOST.

The documentation for this struct was generated from the following file:

- input_plugin.h

3.2 _input_plugin Struct Reference

`#include <input_plugin.h>`

Data Fields

- input_version_type version
- input_flags_type flags
- char * name
- char * author
- void * handle
- input_init_type init
- input_shutdown_type shutdown
- input_plugin_handle_type plugin_handle
- input_can_handle_type can_handle
- input_open_type open
- input_close_type close
- input_play_frame_type play_frame
- input_frame_seek_type frame_seek
- input_frame_size_type frame_size
- input_nr_frames_type nr_frames
- input_frame_to_sec_type frame_to_sec
- input_sample_rate_type sample_rate
- input_channels_type channels
- input_stream_info_type stream_info
- input_nr_tracks_type nr_tracks
- input_track_seek_type track_seek

3.2.1 Field Documentation

3.2.1.1 input_version_type _input_plugin::version

Must be set to INPUT_PLUGIN_VERSION

3.2.1.2 input_flags_type _input_plugin::flags

Fixed flags for the plugin (P_*)

3.2.1.3 char* _input_plugin::name

Should point the a character array containing the name of this plugin

3.2.1.4 char* _input_plugin::author

Should point to a character array containing the name of the author(s) of this plugin.

3.2.1.5 void* _input_plugin::handle

dlopen() handle of this plugin. Filled in by the HOST.

3.2.1.6 input_init_type _input_plugin::init

3.2.1.7 input_shutdown_type _input_plugin::shutdown

3.2.1.8 input_plugin_handle_type _input_plugin::plugin_handle

3.2.1.9 input_can_handle_type _input_plugin::can_handle

3.2.1.10 input_open_type _input_plugin::open

3.2.1.11 input_close_type _input_plugin::close

3.2.1.12 input_play_frame_type _input_plugin::play_frame

3.2.1.13 input_frame_seek_type _input_plugin::frame_seek

3.2.1.14 input_frame_size_type _input_plugin::frame_size

3.2.1.15 input_nr_frames_type _input_plugin::nr_frames

3.2.1.16 input_frame_to_sec_type _input_plugin::frame_to_sec

3.2.1.17 input_sample_rate_type _input_plugin::sample_rate

3.2.1.18 input_channels_type _input_plugin::channels

3.2.1.19 input_stream_info_type _input_plugin::stream_info

3.2.1.20 input_nr_tracks_type _input_plugin::nr_tracks

3.2.1.21 input_track_seek_type _input_plugin::track_seek

The documentation for this struct was generated from the following file:

- input_plugin.h

3.3 _interface_plugin Struct Reference

`#include <interface_plugin.h>`

Data Fields

- interface_version_type version
- char * name
- char * author
- void * handle
- interface_init_type init
- interface_start_type start
- interface_running_type running
- interface_stop_type stop
- interface_close_type close

3.3.1 Field Documentation

3.3.1.1 interface_version_type _interface_plugin::version

3.3.1.2 char* _interface_plugin::name

3.3.1.3 char* _interface_plugin::author

3.3.1.4 void* _interface_plugin::handle

3.3.1.5 interface_init_type _interface_plugin::init

3.3.1.6 interface_start_type _interface_plugin::start

3.3.1.7 interface_running_type _interface_plugin::running

3.3.1.8 interface_stop_type _interface_plugin::stop

3.3.1.9 interface_close_type _interface_plugin::close

The documentation for this struct was generated from the following file:

- interface_plugin.h

3.4 _output_plugin Struct Reference

`#include <output_plugin.h>`

Data Fields

- output_version_type version
- char * name
- char * author
- output_init_type init
- output_open_type open
- output_close_type close
- output_write_type write
- output_start_callbacks_type start_callbacks
- output_set_buffer_type set_buffer
- output_set_sample_rate_type set_sample_rate
- output_get_queue_count_type get_queue_count
- output_get_latency_type get_latency

3.4.1 Field Documentation

3.4.1.1 output_version_type _output_plugin::version

Version of output plugin. Must be OUTPUT_PLUGIN_VERSION

3.4.1.2 char* _output_plugin::name

Name of output plugin

3.4.1.3 char* _output_plugin::author

Author of the plugin

3.4.1.4 output_init_type _output_plugin::init

Initialize output plugin. Called before the plugin is opened for use

3.4.1.5 output_open_type _output_plugin::open

Parameters:

path The path or device designation that should be used

Opens the output plugin. A value of 1 should be returned on success, 0 on failure.

3.4.1.6 output_close_type _output_plugin::close

Close the output plugin

3.4.1.7 output_write_type _output_plugin::write

Parameters:

data Buffer that contains the data Number of bytes that should be read from the buffer

Write out data to the output device. This is a byte count and will typically be the same size as a fragment. A value of 1 should be returned on success, 0 on failure.

3.4.1.8 output_start_callbacks_type _output_plugin::start_callbacks

Parameters:

data pointer to bufs structure in AlsaNode

This function is used for callback based plugins like JACK

3.4.1.9 output_set_buffer_type _output_plugin::set_buffer

Parameters:

frag_size Fragment size to use (in bytes)

frag_count Fragment count to use (in bytes)

channels Number of channels to use

Set up the output device with the given parameters. Some output devices do not accept such configurations in which case they should just be ignored, but still expect frag_size data chunks in the write function. A value of 1 should be returned on success, 0 on failure.

3.4.1.10 output_set_sample_rate_type _output_plugin::set_sample_rate

Parameters:

rate Sample rate to use

Set the sample rate of the output device. A value of 1 should be returned on success, 0 on failure.

3.4.1.11 output_get_queue_count_type _output_plugin::get_queue_count

Returns the number of bytes pending in the hardware buffer of output device. This function is optional.

3.4.1.12 output_get_latency_type _output_plugin::get_latency

Returns the latency of the output device in bytes. This function is optional.

The documentation for this struct was generated from the following file:

- output_plugin.h

3.5 _scope_plugin Struct Reference

`#include <scope_plugin.h>`

Data Fields

- scope_version_type version
- char * name
- char * author
- void * handle
- scope_init_type init
- scope_start_type start
- scope_running_type running
- scope_stop_type stop
- scope_shutdown_type shutdown
- scope_set_data_type set_data
- scope_set_fft_type set_fft

3.5.1 Detailed Description

You should declare a scope_plugin variable and populate it with pointers of the specific functions implemented by your scope

3.5.2 Field Documentation

3.5.2.1 scope_version_type _scope_plugin::version

Set to SCOPE_PLUGIN_VERSION

3.5.2.2 char* _scope_plugin::name

Point to a character array with the name of the scope

3.5.2.3 char* _scope_plugin::author

Point to a character array with the name of the author(s) of the scope

3.5.2.4 void* _scope_plugin::handle

Pointer to a dlopen() handle. This is filled in by the HOST. Set to NULL.

3.5.2.5 scope_init_type _scope_plugin::init

Should point to the implentation of your init() function. Required by the HOST.

3.5.2.6 scope_start_type _scope_plugin::start

Should point to the implementation of your start() function. Required by the HOST.

3.5.2.7 scope_running_type _scope_plugin::running

Should point to the implementation of your running() function. Required by the HOST.

3.5.2.8 scope_stop_type _scope_plugin::stop

Should point to the implementation of your stop() function. Required by the HOST.

3.5.2.9 scope_shutdown_type _scope_plugin::shutdown

Should point to the implementation of your shutdown() function. Required by the HOST.

3.5.2.10 scope_set_data_type _scope_plugin::set_data

Should point to the function that collects PCM data. If you don't want PCM data set to NULL.

3.5.2.11 scope_set_fft_type _scope_plugin::set_fft

Should point to the function that collects FFT data. If you don't want FFT data set to NULL. NB. set_data and set_fft can't both be NULL, at least one must be set.

The documentation for this struct was generated from the following file:

- scope_plugin.h

Chapter 4

File Documentation

4.1 input_plugin.h File Reference

```
#include "stream_info.h"
#include <pthread.h>
```

Data Structures

- struct _input_object
- struct _input_plugin

Defines

- #define P_SEEK 1
- #define P_PERFECTSEEK 2
- #define P_REENTRANT 4
- #define P_FILEBASED 8
- #define P_STREAMBASED 16
- #define P_BUFFERING 32
- #define INPUT_PLUGIN_BASE_VERSION 0x1000
- #define INPUT_PLUGIN_VERSION (INPUT_PLUGIN_BASE_VERSION + 16)

Typedefs

- typedef struct _input_object input_object

- typedef int input_version_type
- typedef int input_flags_type
- typedef int(∗ input_init_type)(void)
- typedef void(∗ input_shutdown_type)(void)
- typedef void ∗ input_plugin_handle_type
- typedef float(∗ input_can_handle_type)(const char ∗path)
- typedef int(∗ input_open_type)(input_object ∗obj, const char ∗path)
- typedef void(∗ input_close_type)(input_object ∗obj)
- typedef int(∗ input_play_frame_type)(input_object ∗obj, char ∗buffer)
- typedef int(∗ input_frame_seek_type)(input_object ∗obj, int frame)
- typedef int(∗ input_frame_size_type)(input_object ∗obj)
- typedef int(∗ input_nr_frames_type)(input_object ∗obj)
- typedef long(∗ input_frame_to_sec_type)(input_object ∗obj, int frame)
- typedef int(∗ input_sample_rate_type)(input_object ∗obj)
- typedef int(∗ input_channels_type)(input_object ∗obj)
- typedef int(∗ input_stream_info_type)(input_object ∗obj, stream_info ∗info)
- typedef int(∗ input_nr_tracks_type)(input_object ∗obj)
- typedef int(∗ input_track_seek_type)(input_object ∗obj, int track)
- typedef struct _input_plugin input_plugin
- typedef input_plugin ∗(∗ input_plugin_info_type)(void)

4.1.1 Define Documentation

4.1.1.1 #define INPUT_PLUGIN_BASE_VERSION 0x1000

The base version number of the scope plugin. Set at 0x1000.

4.1.1.2 #define INPUT_PLUGIN_VERSION (INPUT_PLUGIN_BASE_-VERSION + 16)

The version of the input plugin API. This should be incremented whenever structural changes are made to the API. This value should only be changed by the maintainers.

4.1.1.3 #define P_BUFFERING 32

Set minimal buffer

4.1.1.4 #define P_FILEBASED 8

Set this flag if the stream is file based (local disk file)

4.1.1.5 #define P_PERFECTSEEK 2

Set this flag if your plugin is able to do sample accurate seeking in the stream. This is required for reverse speed playback.

4.1.1.6 #define P_REENTRANT 4

Set this flag if your plugin is reentrant.

4.1.1.7 #define P_SEEK 1

Set this flag if your plugin is able to seek in the stream

4.1.1.8 #define P_STREAMBASED 16

Set this if the stream is a real stream e.g. HTTP or UDP based

4.1.2 Typedef Documentation

4.1.2.1 typedef float(∗ input_can_handle_type)(const char ∗path)

Parameters:

path Path to stream

Returns a rating between 0.0 and 1.0 for how well this plugin can handle the given path 1.0 = Excellent 0.0 = Huh?

4.1.2.2 typedef int(∗ input_channels_type)(input_object ∗obj)

Parameters:

obj input object

Returns number of channels in the stream

4.1.2.3 typedef void(∗ input_close_type)(input_object ∗obj)

Parameters:

obj input object

Close stream

4.1.2.4 typedef int input_flags_type

Capability flags for this plugin

4.1.2.5 typedef int(∗ input_frame_seek_type)(input_object ∗obj, int frame)

Parameters:

obj input object

frame Seek to a specific frame number

4.1.2.6 typedef int(∗ input_frame_size_type)(input_object ∗obj)

Parameters:

obj input object

Returns the frame size in bytes

4.1.2.7 typedef long(∗ input_frame_to_sec_type)(input_object ∗obj,int frame)

Parameters:

obj input object

frame frame number

Returns the offset from the start time in centiseconds (100th of a second) for the frame given.

4.1.2.8 typedef int(∗ input_init_type)(void)

Init plugin

4.1.2.9 typedef int(∗ input_nr_frames_type)(input_object ∗obj)

Parameters:

obj input object

Returns the total number of frames in the stream

4.1.2.10 typedef int(∗ input_nr_tracks_type)(input_object ∗obj)

Parameters:

obj input object

Return number of tracks. Optional

4.1.2.11 typedef struct _input_object input_object

4.1.2.12 typedef int(∗ input_open_type)(input_object ∗obj, const char ∗path)

Parameters:

obj input object

path path of stream to open

Open stream

4.1.2.13 typedef int(∗ input_play_frame_type)(input_object ∗obj, char ∗buffer)

Parameters:

obj input object

buffer buffer where we should write the frame to

Play/decode a single frame. This function should write exactly one frame to the buffer. If there is not enough PCM data to fill the frame it should be padded with zeros (silence).

4.1.2.14 typedef struct _input_plugin input_plugin

4.1.2.15 typedef void∗ input_plugin_handle_type

Handle for plugin. Filled in by the host

4.1.2.16 typedef input_plugin∗(∗ input_plugin_info_type)(void)

Every input plugin should have an input_plugin_info() function that returns a pointer to an input_plugin structure that is set up with pointers to your implementations. If your plugin is compiled using C++ make sure you 'extern "C"' the input_plugin_info() function or else the HOST will not be able to load the plugin.

4.1.2.17 typedef int(∗ input_sample_rate_type)(input_object ∗obj)

Parameters:

obj input object

Returns the sample rate of the stream

4.1.2.18 typedef void(∗ input_shutdown_type)(void)

Prepare the plugin for removal

4.1.2.19 typedef int(∗ input_stream_info_type)(input_object ∗obj, stream_info ∗info)

Parameters:

obj input object

info pointer to stream_info structure

Return stream info of the current stream. You should not allocate space for the stream_-info structure. The HOST will take care of that.

4.1.2.20 typedef int(∗ input_track_seek_type)(input_object ∗obj, int track)

4.1.2.21 typedef int input_version_type

input plugin binary version. Must be set to INPUT_PLUGIN_VERSION

4.2 interface_plugin.h File Reference

```
#include "CorePlayer.h"
#include "Playlist.h"
```

Data Structures

- struct _interface_plugin

Defines

- #define INTERFACE_PLUGIN_BASE_VERSION 0x1000
- #define INTERFACE_PLUGIN_VERSION (INTERFACE_PLUGIN_BASE_-VERSION + 4)

Typedefs

- typedef int interface_version_type
- typedef int(∗ interface_init_type)()
- typedef int(∗ interface_start_type)(Playlist ∗, int, char ∗∗)
- typedef int(∗ interface_running_type)()
- typedef int(∗ interface_stop_type)()
- typedef void(∗ interface_close_type)()
- typedef struct _interface_plugin interface_plugin
- typedef interface_plugin ∗(∗ interface_plugin_info_type)()

4.2.1 Define Documentation

4.2.1.1 #define INTERFACE_PLUGIN_BASE_VERSION 0x1000

4.2.1.2 #define INTERFACE_PLUGIN_VERSION (INTERFACE_PLUGIN_-BASE_VERSION + 4)

4.2.2 Typedef Documentation

4.2.2.1 typedef void(∗ interface_close_type)()

4.2.2.2 typedef int(∗ interface_init_type)()

4.2.2.3 typedef struct _interface_plugin interface_plugin

4.2.2.4 typedef interface_plugin∗(∗ interface_plugin_info_type)()

4.2.2.5 typedef int(∗ interface_running_type)()

4.2.2.6 typedef int(∗ interface_start_type)(Playlist ∗, int, char ∗∗)

4.2.2.7 typedef int(∗ interface_stop_type)()

4.2.2.8 typedef int interface_version_type

4.3 output_plugin.h File Reference

Data Structures

- struct _output_plugin

Defines

- #define OUTPUT_PLUGIN_BASE_VERSION 0x1000
- #define OUTPUT_PLUGIN_VERSION (OUTPUT_PLUGIN_BASE_-VERSION + 6)

Typedefs

- typedef int output_version_type
- typedef int(∗ output_init_type)(void)
- typedef int(∗ output_open_type)(const char ∗path)
- typedef void(∗ output_close_type)(void)
- typedef int(∗ output_write_type)(void ∗data, int byte_count)
- typedef int(∗ output_start_callbacks_type)(void ∗data)
- typedef int(∗ output_set_buffer_type)(int ∗frag_size, int ∗frag_count, int ∗channels)
- typedef unsigned int(∗ output_set_sample_rate_type)(unsigned int rate)
- typedef int(∗ output_get_queue_count_type)(void)
- typedef int(∗ output_get_latency_type)(void)
- typedef struct _output_plugin output_plugin
- typedef output_plugin ∗(∗ output_plugin_info_type)(void)

4.3.1 Define Documentation

4.3.1.1 #define OUTPUT_PLUGIN_BASE_VERSION 0x1000

4.3.1.2 #define OUTPUT_PLUGIN_VERSION (OUTPUT_PLUGIN_BASE_-VERSION + 6)

4.3.2 Typedef Documentation

4.3.2.1 typedef void(∗ output_close_type)(void)

4.3.2.2 typedef int(∗ output_get_latency_type)(void)

4.3.2.3 typedef int(∗ output_get_queue_count_type)(void)

4.3.2.4 typedef int(∗ output_init_type)(void)

4.3.2.5 typedef int(∗ output_open_type)(const char ∗path)

4.3.2.6 typedef struct _output_plugin output_plugin

4.3.2.7 typedef output_plugin∗(∗ output_plugin_info_type)(void)

4.3.2.8 typedef int(∗ output_set_buffer_type)(int ∗frag_size, int ∗frag_count, int ∗channels)

4.3.2.9 typedef unsigned int(∗ output_set_sample_rate_type)(unsigned int rate)

4.3.2.10 typedef int(∗ output_start_callbacks_type)(void ∗data)

4.3.2.11 typedef int output_version_type

4.3.2.12 typedef int(∗ output_write_type)(void ∗data, int byte_count)

4.4 scope_plugin.h File Reference

Data Structures

- struct _scope_plugin

Defines

- #define SCOPE_PLUGIN_BASE_VERSION 0x1000
- #define SCOPE_PLUGIN_VERSION (SCOPE_PLUGIN_BASE_VERSION + 7)
- #define SCOPE_NICE 10
- #define SCOPE_SLEEP 20000
- #define SCOPE_BG_RED 0
- #define SCOPE_BG_GREEN 0
- #define SCOPE_BG_BLUE 0

Typedefs

- typedef int scope_version_type
- typedef int(∗ scope_init_type)(void ∗arg)
- typedef void(∗ scope_start_type)(void)
- typedef int(∗ scope_running_type)(void)
- typedef void(∗ scope_stop_type)(void)
- typedef void(∗ scope_shutdown_type)(void)
- typedef void(∗ scope_set_data_type)(void ∗buffer, int count)
- typedef void(∗ scope_set_fft_type)(void ∗buffer, int samples, int channels)
- typedef struct _scope_plugin scope_plugin
- typedef scope_plugin ∗(∗ scope_plugin_info_type)(void)

4.4.1 Define Documentation

4.4.1.1 #define SCOPE_BG_BLUE 0

The value of the BLUE component of the default background color for scope windows. Value should be from 0-255

4.4.1.2 #define SCOPE_BG_GREEN 0

The value of the GREEN component of the default background color for scope windows. Value should be from 0-255

4.4.1.3 #define SCOPE_BG_RED 0

The value of the RED component of the default background color for scope windows. Value should be from 0-255

4.4.1.4 #define SCOPE_NICE 10

The default nice level scope plugins should be set at. Most scope plugins are just eye candy and as such should not interfere with other processes on your system. They should only use CPU cycles that would otherwise be wasted. Setting the scopes to a nice level of 10 or higher pretty much insures this. If you don't like this policy you can lower the value. Keep in mind that negative values will only work if you run the HOST as root

4.4.1.5 #define SCOPE_PLUGIN_BASE_VERSION 0x1000

The base version number of the scope plugin. Set at 0x1000

4.4.1.6 #define SCOPE_PLUGIN_VERSION (SCOPE_PLUGIN_BASE_-VERSION + 7)

The version of the scope plugin API. This should be increased whenever structural changes are made to the API. This value should only be changed by the maintainers.

4.4.1.7 #define SCOPE_SLEEP 20000

The default sleep time in microseconds for scopes. After every render iteration a scope should sleep for this amount of time. You should use the dosleep() call i.e. dosleep(SCOPE_SLEEP). A value of 20000 will let scopes run at 100000/20000 = 50 frames per second. If the scopes are consuming too much CPU consider raising this value.

4.4.2 Typedef Documentation

4.4.2.1 typedef int(* scope_init_type)(void *arg)

The init function of a scope plugin. This function should initialize all data structures needed for the scope plugin. Return value should be 1 on success, 0 if initialization fails.

Parameters:

Set to NULL. This currently used for internal plugins only

4.4.2.2 typedef struct _scope_plugin scope_plugin

4.4.2.3 typedef scope_plugin*(* scope_plugin_info_type)(void)

Every scope plugin should have a scope_plugin_info() function that returns a pointer to a scope_plugin structure that is filled with pointers to your function implementations.

4.4.2.4 typedef int(* scope_running_type)(void)

This function should tell the HOST if the scope is running i.e. on-screen and rendering. A value of 1 should be returned if this is the case, 0 if the scope is not active.

4.4.2.5 typedef void(* scope_set_data_type)(void *buffer, int count)

Parameters:

buffer pointer to buffer data

count number of short (int16) samples in buffer

The set_data function should be defined if your scope wants to get it hands on PCM data. The format of the buffer is short (int16) interleaved stereo data. A count value of 1024 means there are 2048 short samples in the buffer. These samples are interleaved, so even sample positions are from the left channel, uneven sample positions from the right channel. The API will be changed to accommodate variable channels in the not too distant future.

4.4.2.6 typedef void(* scope_set_fft_type)(void *buffer, int samples, int channels)

Parameters:

buffer buffer with FFT values

samples number of FFT values per channel

channels number of channels

This function should be defined if your scope wants to get FFT data. The HOST typically calculates 256 FFT values per channel (going from low frequency range to high). The value is betwee 0-256. The buffer format is NON-interleaved int (int32). So if samples = 256 and channels = 2 then there are 2 * 256 number of samples in the buffer. The first 256 are for channel 1, the other 256 for channel 2.

4.4.2.7 typedef void(∗ scope_shutdown_type)(void)

The shutdown function is called just before the plugin is unloaded or just before the HOST decides to exit. All data structures allocated in the init routine should be freed here.

4.4.2.8 typedef void(∗ scope_start_type)(void)

This function will be called when the HOST wants to activate the scope. It should pop up the scope window and start rendering the PCM or FFT data

4.4.2.9 typedef void(∗ scope_stop_type)(void)

This function should stop and close the scope window if it was running. It should just return if the scope is not running.

4.4.2.10 typedef int scope_version_type

The API this scope was compiled against. It should always be set to SCOPE_-PLUGIN_VERSION. Failing to set this will most likely result in a scope plugin that won't load.

Index

_input_object, 5
    flags, 5
    frame_size, 6
    local_data, 6
    nr_channels, 6
    nr_frames, 6
    nr_tracks, 6
    object_mutex, 6
    path, 6
    ready, 5
_input_plugin, 7
    author, 7
    can_handle, 8
    channels, 8
    close, 8
    flags, 7
    frame_seek, 8
    frame_size, 8
    frame_to_sec, 8
    handle, 8
    init, 8
    name, 7
    nr_frames, 8
    nr_tracks, 8
    open, 8
    play_frame, 8
    plugin_handle, 8
    sample_rate, 8
    shutdown, 8
    stream_info, 8
    track_seek, 8
    version, 7
_interface_plugin, 9
    author, 9
    close, 9
    handle, 9
    init, 9
    name, 9
    running, 9
    start, 9
    stop, 9
    version, 9
_output_plugin, 10
    author, 10
    close, 11
    get_latency, 12
    get_queue_count, 12
    init, 10
    name, 10
    open, 10
    set_buffer, 11
    set_sample_rate, 11
    start_callbacks, 11
    version, 10
    write, 11
_scope_plugin, 13
    author, 13
    handle, 13
    init, 13
    name, 13
    running, 14
    set_data, 14
    set_fft, 14
    shutdown, 14
    start, 14
    stop, 14
    version, 13

author
    _input_plugin, 7
    _interface_plugin, 9
    _output_plugin, 10
    _scope_plugin, 13

can_handle
_input_plugin, 8
channels
_input_plugin, 8
close
_input_plugin, 8
_interface_plugin, 9
_output_plugin, 11

flags
_input_object, 5
_input_plugin, 7
frame_seek
_input_plugin, 8
frame_size
_input_object, 6
_input_plugin, 8
frame_to_sec
_input_plugin, 8

get_latency
_output_plugin, 12
get_queue_count
_output_plugin, 12

handle
_input_plugin, 8
_interface_plugin, 9
_scope_plugin, 13

init
_input_plugin, 8
_interface_plugin, 9
_output_plugin, 10
_scope_plugin, 13
input_can_handle_type
input_plugin.h, 17
input_channels_type
input_plugin.h, 17
input_close_type
input_plugin.h, 17
input_flags_type
input_plugin.h, 17
input_frame_seek_type
input_plugin.h, 18
input_frame_size_type
input_plugin.h, 18
input_frame_to_sec_type
input_plugin.h, 18
input_init_type
input_plugin.h, 18
input_nr_frames_type
input_plugin.h, 18
input_nr_tracks_type
input_plugin.h, 18
input_object
input_plugin.h, 19
input_open_type
input_plugin.h, 19
input_play_frame_type
input_plugin.h, 19
input_plugin
input_plugin.h, 19
input_plugin.h, 15
input_can_handle_type, 17
input_channels_type, 17
input_close_type, 17
input_flags_type, 17
input_frame_seek_type, 18
input_frame_size_type, 18
input_frame_to_sec_type, 18
input_init_type, 18
input_nr_frames_type, 18
input_nr_tracks_type, 18
input_object, 19
input_open_type, 19
input_play_frame_type, 19
input_plugin, 19
INPUT_PLUGIN_BASE_-
VERSION, 16
input_plugin_handle_type, 19
input_plugin_info_type, 19
INPUT_PLUGIN_VERSION, 16
input_sample_rate_type, 19
input_shutdown_type, 20
input_stream_info_type, 20
input_track_seek_type, 20
input_version_type, 20
P_BUFFERING, 16
P_FILEBASED, 16
P_PERFECTSEEK, 16
P_REENTRANT, 17

P_SEEK, 17
P_STREAMBASED, 17
INPUT_PLUGIN_BASE_VERSION
input_plugin.h, 16
input_plugin_handle_type
input_plugin.h, 19
input_plugin_info_type
input_plugin.h, 19
INPUT_PLUGIN_VERSION
input_plugin.h, 16
input_sample_rate_type
input_plugin.h, 19
input_shutdown_type
input_plugin.h, 20
input_stream_info_type
input_plugin.h, 20
input_track_seek_type
input_plugin.h, 20
input_version_type
input_plugin.h, 20
interface_close_type
interface_plugin.h, 22
interface_init_type
interface_plugin.h, 22
interface_plugin
interface_plugin.h, 22
interface_plugin.h, 21
interface_close_type, 22
interface_init_type, 22
interface_plugin, 22
INTERFACE_PLUGIN_BASE_-
VERSION, 22
interface_plugin_info_type, 22
INTERFACE_PLUGIN_-
VERSION, 22
interface_running_type, 22
interface_start_type, 22
interface_stop_type, 22
interface_version_type, 22
INTERFACE_PLUGIN_BASE_-
VERSION
interface_plugin.h, 22
interface_plugin_info_type
interface_plugin.h, 22
INTERFACE_PLUGIN_VERSION
interface_plugin.h, 22
interface_running_type
interface_plugin.h, 22
interface_start_type
interface_plugin.h, 22
interface_stop_type
interface_plugin.h, 22
interface_version_type
interface_plugin.h, 22

local_data
_input_object, 6

name
_input_plugin, 7
_interface_plugin, 9
_output_plugin, 10
_scope_plugin, 13
nr_channels
_input_object, 6
nr_frames
_input_object, 6
_input_plugin, 8
nr_tracks
_input_object, 6
_input_plugin, 8

object_mutex
_input_object, 6
open
_input_plugin, 8
_output_plugin, 10
output_close_type
output_plugin.h, 24
output_get_latency_type
output_plugin.h, 24
output_get_queue_count_type
output_plugin.h, 24
output_init_type
output_plugin.h, 24
output_open_type
output_plugin.h, 24
output_plugin
output_plugin.h, 24
output_plugin.h, 23
output_close_type, 24
output_get_latency_type, 24

output_get_queue_count_type, 24
output_init_type, 24
output_open_type, 24
output_plugin, 24
OUTPUT_PLUGIN_BASE_-VERSION, 24
output_plugin_info_type, 24
OUTPUT_PLUGIN_VERSION, 24
output_set_buffer_type, 24
output_set_sample_rate_type, 24
output_start_callbacks_type, 24
output_version_type, 24
output_write_type, 24
OUTPUT_PLUGIN_BASE_-VERSION
output_plugin.h, 24
output_plugin_info_type
output_plugin.h, 24
OUTPUT_PLUGIN_VERSION
output_plugin.h, 24
output_set_buffer_type
output_plugin.h, 24
output_set_sample_rate_type
output_plugin.h, 24
output_start_callbacks_type
output_plugin.h, 24
output_version_type
output_plugin.h, 24
output_write_type
output_plugin.h, 24

P_BUFFERING
input_plugin.h, 16
P_FILEBASED
input_plugin.h, 16
P_PERFECTSEEK
input_plugin.h, 16
P_REENTRANT
input_plugin.h, 17
P_SEEK
input_plugin.h, 17
P_STREAMBASED
input_plugin.h, 17
path
_input_object, 6
play_frame
_input_plugin, 8
plugin_handle
_input_plugin, 8

ready
_input_object, 5
running
_interface_plugin, 9
_scope_plugin, 14

sample_rate
_input_plugin, 8
SCOPE_BG_BLUE
scope_plugin.h, 25
SCOPE_BG_GREEN
scope_plugin.h, 25
SCOPE_BG_RED
scope_plugin.h, 25
scope_init_type
scope_plugin.h, 26
SCOPE_NICE
scope_plugin.h, 26
scope_plugin
scope_plugin.h, 27
scope_plugin.h, 25
SCOPE_BG_BLUE, 25
SCOPE_BG_GREEN, 25
SCOPE_BG_RED, 25
scope_init_type, 26
SCOPE_NICE, 26
scope_plugin, 27
SCOPE_PLUGIN_BASE_-VERSION, 26
scope_plugin_info_type, 27
SCOPE_PLUGIN_VERSION, 26
scope_running_type, 27
scope_set_data_type, 27
scope_set_fft_type, 27
scope_shutdown_type, 27
SCOPE_SLEEP, 26
scope_start_type, 28
scope_stop_type, 28
scope_version_type, 28

SCOPE_PLUGIN_BASE_VERSION
    scope_plugin.h, 26
scope_plugin_info_type
    scope_plugin.h, 27
SCOPE_PLUGIN_VERSION
    scope_plugin.h, 26
scope_running_type
    scope_plugin.h, 27
scope_set_data_type
    scope_plugin.h, 27
scope_set_fft_type
    scope_plugin.h, 27
scope_shutdown_type
    scope_plugin.h, 27
SCOPE_SLEEP
    scope_plugin.h, 26
scope_start_type
    scope_plugin.h, 28
scope_stop_type
    scope_plugin.h, 28
scope_version_type
    scope_plugin.h, 28
set_buffer
    _output_plugin, 11
set_data
    _scope_plugin, 14
set_fft
    _scope_plugin, 14
set_sample_rate
    _output_plugin, 11
shutdown
    _input_plugin, 8
    _scope_plugin, 14
start
    _interface_plugin, 9
    _scope_plugin, 14
start_callbacks
    _output_plugin, 11
stop
    _interface_plugin, 9
    _scope_plugin, 14
stream_info
    _input_plugin, 8

track_seek
    _input_plugin, 8

version
    _input_plugin, 7
    _interface_plugin, 9
    _output_plugin, 10
    _scope_plugin, 13

write
    _output_plugin, 11